

CLAIMS

1. A method for processing a substrate, comprising:
generating a fluid meniscus to process the substrate;
applying the fluid meniscus to a surface of the substrate; and
5 managing a substrate processing environment so evaporation of fluids from a surface in the substrate processing environment is reduced.
2. A method for processing a substrate as recited in claim 1, wherein
managing the substrate processing environment comprises inputting a gas into the
10 substrate processing environment to reduce an evaporation rate of fluids within the substrate processing environment.
3. A method for processing a substrate as recited in claim 2, wherein the gas
has a high relative humidity.
15
4. A method for processing a substrate as recited in claim 3, wherein the gas
with the high relative humidity is generated by transmitting gas into a liquid bath and
capturing vapor that bubbles up through the liquid bath.
- 20 5. A method for processing a substrate as recited in claim 3, wherein the gas
with the high relative humidity has a relative humidity between about 50% and about
100%.

6. A method for processing a substrate as recited in claim 3, wherein the gas with the high relative humidity has a relative humidity between about 90% and about 100%.

5

7. A method for processing a substrate as recited in claim 3, wherein the gas with the high relative humidity has a relative humidity of about 100%.

8. A method for processing a substrate as recited in claim 2, wherein
10 managing the substrate processing environment further comprises detecting fluid thickness on the fluid surface.

9. A method for processing a substrate as recited in claim 2, wherein the gas maintains a concentration of a particular liquid in water.

15

10. A method for processing a substrate as recited in claim 9, wherein the particular liquid is one of an alcohol, an acetone, and an azeotropic mixture.

11. A method for processing a substrate as recited in claim 9, wherein the
20 particular liquid is isopropyl alcohol (IPA).

12. A method for processing a substrate as recited in claim 9, wherein the gas that maintains a concentration of the particular liquid in water is an N₂ carrier gas containing isopropyl alcohol (IPA) in vapor form.

5 13. An apparatus for processing a substrate, comprising:
a proximity head capable of generating a fluid meniscus to process a substrate surface; and
a chamber configured to house the proximity head, the chamber also configured to be supplied with an environmental control gas.

10

14 An apparatus for processing a substrate as recited in claim 13 further comprising,
a wafer processing environment generator configured to generate the environmental control gas.

15

15. An apparatus for processing a substrate as recited in claim 13, wherein the wafer processing environment generator is a bubbler.

16. An apparatus for processing a substrate as recited in claim 15, wherein the
20 bubbler is configured to input a gas into a liquid bath and further configured to capture the gas that has traveled through the liquid bath.

17. An apparatus for processing a substrate as recited in claim 13, wherein the environmental control gas is a high relative humidity gas.

18. An apparatus for processing a substrate as recited in claim 13, wherein the environmental control gas maintains a concentration of a particular liquid in water.

19. An apparatus for processing a substrate as recited in claim 18, wherein the particular liquid is one of isopropyl alcohol, DIW and IPA, alcohol, DIW and alcohol, ketone, and ether.

10

20. An apparatus for processing a substrate, comprising:

a proximity head capable of generating a fluid meniscus to process a substrate surface; and

an opening located on the surface of the proximity head configured to apply an environmental control gas to a region on a leading edge side of the proximity head.

15

21. An apparatus for processing a substrate as recited in claim 20, wherein the environmental control gas reduces an evaporation rate of fluids from a surface of the proximity head.

20

22. An apparatus for processing a substrate as recited in claim 20, wherein the environmental control gas is a high relative humidity gas.

23. An apparatus for processing a substrate as recited in claim 20, wherein the gas with a high relative humidity has a relative humidity between about 50% and about 100%.

5

24. An apparatus for processing a substrate as recited in claim 22, wherein the gas with the high relative humidity has a relative humidity between about 90% and about 100%.

10

25. An apparatus for processing a substrate as recited in claim 22, wherein the gas with the high relative humidity has a relative humidity of about 100%.

26. An apparatus for processing a substrate as recited in claim 20, wherein the environmental control gas maintains a concentration of a particular liquid in water.

15

27. A method for processing a substrate, comprising:

generating a fluid meniscus to process the substrate;

applying the fluid meniscus to a surface of the substrate; and

reducing evaporation of fluids from a surface in the substrate processing

20 environment.

28. A method for processing a substrate as recited in claim 27, wherein reducing evaporation of fluids includes managing a substrate processing environment by inputting a high relative humidity gas into the substrate processing environment.

5 29. A method for processing a substrate as recited in claim 28, wherein the gas with the high relative humidity is generated by transmitting gas into a liquid bath and capturing vapor that bubbles up through the liquid bath.

30. A method for processing a substrate as recited in claim 28, wherein the gas
10 with the high relative humidity has a relative humidity between about 50% and about 100%.

31. A method for processing a substrate as recited in claim 28, wherein the gas
with the high relative humidity has a relative humidity between about 90% and about
15 100%.

32. A method for processing a substrate as recited in claim 28, wherein the gas with the high relative humidity has a relative humidity of about 100%.